

Task A. Hills

Welcome to Innopolis city. Throughout the whole year, Innopolis citizens suffer from everlasting city construction.

From the window in your room, you see the sequence of n hills, where i -th of them has height a_i . Innopolis administration wants to build some houses on the hills. However, for the sake of city appearance, a house can be only built on the hill, which is strictly higher than neighbouring hills (if they are present). For example, if the sequence of heights is $5, 4, 6, 2$, then houses could be built on hills with heights 5 and 6 only.

Innopolis administration has an excavator, that can decrease the height of an arbitrary hill by one in one hour. The excavator can only work on one hill at a time. It is allowed to decrease hills up to zero height, or even to negative values. Increasing the height of any hill is impossible. The city administration wants to build k houses, so there must be at least k hills that satisfy the condition above. What is the minimum time required to adjust the hills to achieve the administration's plan?

However, the exact value of k is not yet determined, so could you please calculate the answers for all k in range $1 \leq k \leq \lceil \frac{n}{2} \rceil$? Here $\lceil \frac{n}{2} \rceil$ denotes n divided by two, rounded up.

Input

The first line of the input contains the only integer n ($1 \leq n \leq 5000$): the number of hills in the sequence.

The second line contains n integers a_i ($1 \leq a_i \leq 100\,000$): the heights of hills in the sequence.

Output

Print exactly $\lceil \frac{n}{2} \rceil$ numbers separated by spaces. The i -th printed number should be equal to the minimum number of hours required to level hills so it becomes possible to build i houses.

Scoring

This problem contains six subtasks, for each subtask you will get the points only if you pass all the tests for this subtask.

1. (7 points) $n = 3$, $a_i \leq 100$
2. (15 points) $n \leq 10$, $a_i \leq 100$
3. (13 points) $n \leq 100$, $a_i \leq 100$

4. (18 points) $n \leq 100$, $a_i \leq 2000$
5. (22 points) $n \leq 500$
6. (25 points) $n \leq 5000$

Examples

Example 1

Input:

```
5
1 1 1 1 1
```

Output:

```
1 2 2
```

To get at least one hill suitable for construction, one can decrease the second hill by one in one hour, then the sequence of heights becomes 1, 0, 1, 1, 1 and the first hill becomes suitable for construction.

To get at least two or at least three suitable hills, one can decrease the second and the fourth hills, then the sequence of heights becomes 1, 0, 1, 0, 1, and hills 1, 3, 5 become suitable for construction.

Example 2

Input:

```
3
1 2 3
```

Output:

```
0 2
```

Example 3

Input:

```
5
1 2 3 2 2
```

Output:

```
0 1 3
```